

# MAXX 2613



		
4 - 14 years	50 kids	231,4 m <sup>2</sup>



## Material specification

- Hot-dip galvanized and powder coated construction of 200 x 120 mm profile,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Transparent polycarbonate panels with a weather-resistant print,
- Covers made of hot-dip galvanized and powder coated steel mesh,
- Side panels made of Robinia - very durable acacia wood without sharp edges, resistant to weather conditions
- Stainless steel tube slide,
- Elements made of safe, certified rubber with textile reinforcement,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel screws and/or screws covered with plastic caps,



## Physical development



sliding



observation



community



passage



climbing





## Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		110

## Product technical sheet

# MAXX 2613

### Amount of safe surface corresponding with free fall height:

HIC <60	117,7 m <sup>2</sup>
HIC 90	13,4 m <sup>2</sup>
HIC 100	63,3 m <sup>2</sup>
HIC 105	19,6 m <sup>2</sup>
HIC 110	17,4 m <sup>2</sup>

Data is subject to change without prior notice.

