



Product technical sheet

MAXX 2902



4 - 14 years



30 kids



81,9 m²



Material specification

- Hot-dip galvanized and powder coated steel construction with a diameter of 160 mm,
- Hot-dip galvanized and powder coated steel construction with a diameter of 220 mm,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Side panels made of durable HPL plate, resistant to weather conditions,
- Covers made of stainless steel,
- Stainless steel tube slide,
- Elements made of safe, certified rubber with textile reinforcement,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development



balance



hiding



sliding



community



climbing





1
number of towers



1
number of slides



2
number of activity elements

Product technical sheet

MAXX 2902


Product data

Length	925 cm
Width	550 cm
Total height	1150 cm
Age group	4 - 14 years
Number of users	30 kids
Safety zone	81,9 m ²
Free fall height	100 cm
The height of the platforms	850 cm
tube slide platform height	850 cm
In accordance with norm EN	1176-1:2017+A1:2023
Availability of spare parts	YES



Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;



81,9 m²



Guarantee

30 30 year guarantee - Durability of steel and stainless steel structural elements

15 15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements

10 10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)

5 5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card



Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

Product technical sheet

MAXX 2902

Amount of safe surface corresponding with free fall height:

HIC <60 50,1 m²

HIC 100 31,8 m²

Data is subject to change without prior notice.

