


ROXX 3503



4 - 14 years



18 kids



47,9 m²

Material specification

- Hot-dip galvanized steel construction,
- Side panels made of durable HPL plate, resistant to weather conditions,
- Climbing stones made of durable HPL plate, resistant to weather conditions,
- Stainless steel screws and/or screws covered with plastic caps,




Physical development





climbing





47,9 m²



Product technical sheet

ROXX 3503

Product data

Length	470 cm
Width	250 cm
Total height	290 cm
Age group	4 - 14 years
Number of users	18 kids
Safety zone	47,9 m²
Free fall height	290 cm
In accordance with norm EN	1176-1:2017+A1:2023
Availability of spare parts	YES

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee

30

30 year guarantee - Durability of steel and stainless steel structural elements

15

15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements

10

10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)

5

5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card



Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		290

Product technical sheet

ROXX 3503

Amount of safe surface corresponding with free fall height:

HIC 185 10,8 m²

HIC 290 37,1 m²

Data is subject to change without prior notice.

